NSN 5935-00-848-7452

Body Style:

Aluminum alloy

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-848-7452

Hood, side opening w/clamp
Overall Length:
2.625 inches
Overall Height:
2.406 inches
Overall Width:
0.500 inches
Cable Entrance Diameter:
0.656 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
41 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Shell Type: Hood, side opening
Hood, side opening
Hood, side opening Connector Locking Method:
Hood, side opening Connector Locking Method: Jackscrew-socket
Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method:
Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp
Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Thread Size:
Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Thread Size: 0.112 inches
Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Thread Size: 0.112 inches Terminal Location:
Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Thread Size: 0.112 inches Terminal Location: Back single mating end single contact grouping
Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Thread Size: 0.112 inches Terminal Location: Back single mating end single contact grouping Contact Material:
Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Thread Size: 0.112 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Thread Size: 0.112 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Thread Size: 0.112 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Thread Size: 0.112 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Thread Size: 0.112 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic melamine single mating end

NSN 5935-00-848-7452Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Anodize
Included Contact Quantity:
41 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.041 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A039b0