NSN 5935-00-849-0802

Telephone Jack - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-00-849-0802

Electrical Insulation Feature:

Electrical Insulation Feature:
Insulated completely
Body Style:
In-line straight
Overall Length:
2.156 inches
Overall Diameter:
0.688 inches
Cable Entrance Diameter:
0.281 inches
Bushing Accommodation Hole Shape:
Round
Accommodated Finger Type:
Three conductor, cone tip single finger
Finger Accommodation Diameter:
0.250 inches single finger
Finger Accommodation Length:
1.188 inches single finger
Jack Contact Arrangement Designator:
J2
J2 Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 1 bushing
Mounting Facility Type And Quantity: 1 bushing Terminal Type:
Mounting Facility Type And Quantity: 1 bushing Terminal Type: Screw
Mounting Facility Type And Quantity: 1 bushing Terminal Type: Screw Material:
Mounting Facility Type And Quantity: 1 bushing Terminal Type: Screw Material: Plastic, phenol-formaldehyde insulator
Mounting Facility Type And Quantity: 1 bushing Terminal Type: Screw Material: Plastic, phenol-formaldehyde insulator Material:
Mounting Facility Type And Quantity: 1 bushing Terminal Type: Screw Material: Plastic, phenol-formaldehyde insulator Material: Plastic phenol-formaldehyde insulator
Mounting Facility Type And Quantity: 1 bushing Terminal Type: Screw Material: Plastic, phenol-formaldehyde insulator Material: Plastic phenol-formaldehyde insulator Surface Treatment:
Mounting Facility Type And Quantity: 1 bushing Terminal Type: Screw Material: Plastic, phenol-formaldehyde insulator Material: Plastic phenol-formaldehyde insulator Surface Treatment: Tin terminal
Mounting Facility Type And Quantity: 1 bushing Terminal Type: Screw Material: Plastic, phenol-formaldehyde insulator Material: Plastic phenol-formaldehyde insulator Surface Treatment: Tin terminal Surface Treatment:
Mounting Facility Type And Quantity: 1 bushing Terminal Type: Screw Material: Plastic, phenol-formaldehyde insulator Material: Plastic phenol-formaldehyde insulator Surface Treatment: Tin terminal Surface Treatment: Nickel spring
Mounting Facility Type And Quantity: 1 bushing Terminal Type: Screw Material: Plastic, phenol-formaldehyde insulator Material: Plastic phenol-formaldehyde insulator Surface Treatment: Tin terminal Surface Treatment: Nickel spring Shelf Life:
Mounting Facility Type And Quantity: 1 bushing Terminal Type: Screw Material: Plastic, phenol-formaldehyde insulator Material: Plastic phenol-formaldehyde insulator Surface Treatment: Tin terminal Surface Treatment: Nickel spring Shelf Life: N/a
Mounting Facility Type And Quantity: 1 bushing Terminal Type: Screw Material: Plastic, phenol-formaldehyde insulator Material: Plastic phenol-formaldehyde insulator Surface Treatment: Tin terminal Surface Treatment: Nickel spring Shelf Life: N/a

Fiig:

A03400