Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-849-3182

Thread Class:	
2g	
Thread Pitch Diameters:	
+1.490/+1.500 inches	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, external coupling w/backshell	
Overall Length:	
2.703 inches	
Overall Height:	
1.750 inches	
Overall Width:	
1.750 inches	
Environmental Protection:	
Moisture resistant	
Unthreaded Mounting Hole Diameter:	
0.171 inches	
Center To Center Distance Between Mounting Facilities Parallel To Heigh	. +-
1.375 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Wi	dth
1.375 inches	un.
Distance From Mounting Shoulder To Front Face:	
1.005 inches	
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
1	
Contract Desition Amongsment Styles	
Contact Position Arrangement Style:	
12-317 single mating end	
12-317 single mating end	
12-317 single mating end Contact Removability:	
12-317 single mating end Contact Removability: Removable single mating end single contact grouping	
12-317 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps:	
12-317 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping	
12-317 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts:	
 12-317 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping 	
 12-317 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 	
 12-317 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping 	
 12-317 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Polarization Method: 	
12-317 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway	

Electrical Receptacle Connector - Page 2 of 2



Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Thread Length:** 1.005 inches Thready Qty Per Inch (tpi): 8 Thread Size: 1.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 10 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.010 gold grains, troy and 0.010 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Special acme Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0