

View Online at <https://aerobasegroup.com/nsn/5935-00-850-0471>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape

**Overall Length:**

2.289 inches

**Overall Height:**

0.859 inches

**Overall Width:**

1.129 inches

**Environmental Protection:**

Salt water resistant

**Distance Between Mounting Facility Centers:**

1.976 inches

**Threaded Device Type:**

Mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

58 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

20.0 single mating end 1st contact grouping

**Polarization Method:**

Guide pin/socket

**Connector Locking Method:**

Friction

**Thread Length:**

0.266 inches

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.112 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings

**Insert Material:**

Plastic melamine mineral filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end all contact groupings

**Terminal Type:**

Solder well single mating end all contact groupings

**Unable To Decode:**

Unable to decode and unable to decode

**Included Contact Quantity:**

8 single mating end 1st contact grouping

**Included Contact Type:**

Round socket single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.058 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.