Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-850-4402

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, flange mount, external coupling	
Overall Length:	
1.828 inches	
Overall Height:	
Between 2.219 inches and 2.281 inches	
Overall Width:	
Between 2.219 inches and 2.281 inches	
Unthreaded Mounting Hole Diameter:	
Between 0.168 inches and 0.178 inches	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
Between 1.745 inches and 1.755 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
Between 1.745 inches and 1.755 inches	
Cable Entrance Diameter:	
1.708 inches	
Distance From Mounting Shoulder To Front Face:	
Between 0.875 inches and 0.885 inches	
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
32-9 single mating end	
Contact Removability:	
Nonremovable single mating end all contact groupings	
Contact Maximum Current Rating In Amps:	
80.0 single mating end 1st contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
900.0 single mating end all contact groupings	
Contact Maximum Dc Voltage Rating In Volts:	
1250.0 single mating end all contact groupings	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
0.0	
Shell Type:	
Solid	

Electrical Receptacle Connector - Page 2 of 2



Connector Locking Method:
Externally threaded shell
Connector Cable Strain Relief Method:
Potting type
Thread Length:
0.625 inches
Thready Qty Per Inch (tpi):
18
Thread Size:
2.000 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Silver single mating end all contact groupings
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
2 single mating end 1st contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.032 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0