Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-850-6619

# Body Style:

Straight shape, external coupling

## **Overall Length:**

0.887 inches

# **Overall Height:**

1.438 inches

### **Overall Width:**

1.438 inches

#### **Environmental Protection:**

Moisture proof

### **Unthreaded Mounting Hole Diameter:**

Between 0.145 inches and 0.155 inches

### Center To Center Distance Between Mounting Facilities Parallel To Height:

1.125 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.125 inches

## Distance From Mounting Shoulder To Front Face:

Between 0.462 inches and 0.472 inches

## Mating End Quantity:

1

### **Contact Position Arrangement Style:**

16-26 single mating end

### **Contact Removability:**

Nonremovable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

### Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

## Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

### **Polarization Method:**

Key, multiple key groove

#### **Insert Position In Deg:**

146.0

#### Shell Type:

Solid

### **Connector Locking Method:**

Bayonet pin

### **Terminal Location:**

Back single mating end single contact grouping

### **Insert Material:**

Rubber single mating end



## **Terminal Type:**

Solder well single mating end single contact grouping

#### Shell Material:

Aluminum alloy

# Included Contact Quantity:

26 single mating end single contact grouping

# Included Contact Type:

Round socket single mating end single contact grouping

#### Shelf Life:

N/a

### Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A039b0