

View Online at <https://aerobasegroup.com/nsn/5935-00-850-8551>

Thread Class:

2a

Thread Direction:

Right-hand

Overall Length:

0.730 inches

Overall Diameter:

0.810 inches

Environmental Protection:

Vibration resistant

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0

Shell Type:

Potting

Connector Locking Method:

Latch

Connector Cable Strain Relief Method:

Potting type

Thread Size:

0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel and chromium

Included Contact Quantity:

6 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.006 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0