NSN 5935-00-851-2635

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-851-2635

Thread	Class:
Incau	01035.

2a and 2a

Thread Direction:

Right-hand

Body Style:

Straight shape w/flange

Overall Length:

2.125 inches

Overall Height:

2.250 inches

Overall Width:

2.250 inches

Unthreaded Mounting Hole Diameter:

Between 0.171 inches and 0.177 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.750 inches

Distance From Mounting Shoulder To Front Face:

Between 0.975 inches and 0.985 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

32-6 all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

80.0 2nd mating end 1st contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

700.0 all mating ends all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

NSN 5935-00-851-2635

Connector Adapter - Page 2 of 2



Thread Length: 0.625 inches Thready Qty Per Inch (tpi): 18 **Thread Size:** 0.086 inches **Contact Material:** Copper alloy all mating ends all contact groupings **Contact Surface Treatment:** Silver all mating ends all contact groupings **Insert Material:** Rubber all mating ends Shell Material: Aluminum alloy **Shell Surface Treatment:** Anodize **Included Contact Type:** Round socket 1st mating end all contact groupings **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.086 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Uns Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0