## NSN 5935-00-851-8456

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-851-8456

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Round flange mount, external coupling
Overall Length:
1.500 inches
Bushing Diameter:
1.093 inches
Mounting Hole Circle Radius:
Between 1.120 inches and 1.130 inches
Overall Diameter:
2.750 inches
<b>Environmental Protection:</b>
Salt water resistant
Unthreaded Mounting Hole Diameter:
0.204 inches
Distance From Mounting Shoulder To Rear Face:
0.391 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
16s-8 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):

10

## NSN 5935-00-851-8456

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
1.375 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
5 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.005 gold grains, troy and 0.005 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0