

View Online at <https://aerobasegroup.com/nsn/5935-00-851-9805>

Body Style:

Straight shape w/flange

Overall Length:

Between 1.325 inches and 1.336 inches

Overall Height:

Between 1.656 inches and 1.688 inches

Overall Width:

Between 1.656 inches and 1.688 inches

Environmental Protection:

Pressure proof

Unthreaded Mounting Hole Diameter:

Between 0.145 inches and 0.155 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.297 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.297 inches

Distance From Mounting Shoulder To Front Face:

Between 0.688 inches and 0.698 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

20-16 all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Current Rating In Amps:

22.0 all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 all mating ends single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1250.0 all mating ends single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping and silver all mating ends single contact grouping

Insert Material:

Rubber all mating ends

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

16 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.032 gold grains, troy and 0.032 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0