NSN 5935-00-853-3378

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-853-3378 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.938 inches **Overall Height:** 1.625 inches **Overall Width:** 1.625 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 22-18 single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 22.0 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end 2nd contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end 1st contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 80.0 Shell Type: Solid

Connector Locking Method: Externally threaded shell

NSN 5935-00-853-3378

Electrical Receptacle Connector - Page 2 of 2



| Thready Qty Per Inch (tpi): |
|---|
| 18 |
| Thread Size: |
| 1.375 inches |
| Terminal Location: |
| Back single mating end all contact groupings |
| Terminal Type: |
| Solder well single mating end all contact groupings |
| Shell Material: |
| Aluminum alloy |
| Included Contact Quantity: |
| 5 single mating end 2nd contact grouping |
| Included Contact Type: |
| Round socket single mating end all contact groupings |
| Test Data Document: |
| 81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Unef |
| Specification Data: |
| 81349-mil-c-5015 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |
| |
| |