NSN 5935-00-853-6132

Thread Class: 2a and 2b

Thread Direction:

Overall Length: 1.562 inches Overall Height: 0.859 inches Overall Width: 0.438 inches

Right-hand and right-hand

Environmental Protection:

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-853-6132

Explosion proof and salt water resistant and watertight
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
20 20-20 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
2500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
3500.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Potting
Connector Locking Method:
Jackscrew-socket
Connector Cable Strain Relief Method:
Potting type
Thread Size:
0.138 inches and 0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping

NSN 5935-00-853-6132Electrical Plug Connector - Page 2 of 2



Insert Material:
Plastic melamine mineral filled single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Anodize
Included Contact Quantity:
20 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.020 gold grains, troy and 0.020 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0