NSN 5935-00-854-3079

Aluminum alloy

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-854-3079

Body Style:
Angle shape w/cable clamp
Overall Length:
0.879 inches
Overall Height:
1.033 inches
Overall Diameter:
0.666 inches
Body Angle In Deg:
90.0
Environmental Protection:
Humidity resistant and salt water resistant and vibration proof
Mating End Quantity:
1
Contact Position Arrangement Style:
3 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Spring friction
Connector Cable Strain Relief Method:
Compression nut
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:

NSN 5935-00-854-3079Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Anodize
ncluded Contact Quantity:
3 single mating end single contact grouping
ncluded Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.003 gold grains, troy and 0.003 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
18876-10180805 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Specification Data:
18876-10180805 manufacturers specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A039b0