

View Online at <https://aerobasegroup.com/nsn/5935-00-855-2612>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Height:

0.859 inches

Overall Width:

0.875 inches

Distance Between Mounting Facility Centers:

2.281 inches

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

50 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

3200.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

4450.0 single mating end single contact grouping

Connector Locking Method:

Latch

Connector Cable Strain Relief Method:

Cable clamp

Thread Length:

0.266 inches

Thread Size:

0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic melamine mineral filled single mating end

Terminal Type:

Solder well single mating end single contact grouping

Included Contact Quantity:

50 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.050 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0