

View Online at <https://aerobasegroup.com/nsn/5935-00-855-4318>

Body Style:

Straight edge type w/mounting flange

Overall Length:

3.654 inches

Overall Height:

0.660 inches

Overall Width:

0.343 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.142 inches

Distance Between Mounting Facility Centers:

3.406 inches

Board Accommodated Length:

2.972 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.070 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bridged contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty mdg military specification single material response single mating end

Included Contact Quantity:

18 single mating end single contact grouping

Included Contact Type:

Spring pincers single mating end single contact grouping

Special Features:

Contact surface 0.0001 min thk gold plate

Precious Material And Location:

Contact surface gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.