

View Online at <https://aerobasegroup.com/nsn/5935-00-855-8772>

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.906 inches

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Environmental Protection:

Heat resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.906 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.906 inches

Distance From Mounting Shoulder To Front Face:

0.637 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Size:

0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Nickel alloy single mating end single contact grouping

Contact Surface Treatment:

Tin single mating end single contact grouping

Insert Material:

Glass single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Shell Material:

Steel

Shell Surface Treatment:

Tin

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Hermetic seal

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0