Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-857-2009

## **Body Style:**

Straight edge type w/mounting flange

**Overall Length:** 

6.469 inches

## **Overall Height:**

0.626 inches

**Overall Width:** 

0.438 inches

#### **Unthreaded Mounting Hole Diameter:**

0.125 inches

#### **Distance Between Mounting Facility Centers:**

6.219 inches

#### **Board Accommodated Length:**

5.766 inches single board

#### **Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

## Mating End Quantity:

1

## Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

## Contact Removability:

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

10.0 single mating end single contact grouping

#### **Polarization Method:**

Contact

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

# **Insert Material:**

Plastic diallyl phthalate single mating end

# Contact Surface Treatment Specification:

Mil-g-14548 military specification 1st treatment response single mating end single contact grouping and qq-s-365, type 2, grade a federal

specification 2nd treatment response single mating end single contact grouping

# Criticality Code Justification:

Feat

# **Terminal Type:**

Pin single mating end single contact grouping

# **Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping



# **Insert Material Specification:** Mil-m-19833, type gdi-30 military specification single material response single mating end **Included Contact Quantity:** 72 single mating end single contact grouping Included Contact Type: Leaf spring single mating end single contact grouping **Special Features:** Polarized at position 18 and 32 **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.072 gold grains, troy and 0.072 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard):

Mil-g-14548 spec.