Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-857-6692

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
2.000 inches
Overall Height:
0.840 inches
Overall Width:
0.440 inches
Distance Between Mounting Facility Centers:
Between 1.683 inches and 1.693 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
16 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Thread Length:
0.156 inches
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Back single mating end 2nd contact grouping
Contact Material:
Copper alloy single mating end 2nd contact grouping
Contact Surface Treatment:
Gold single mating end 2nd contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end
Terminal Type:
Only and the second on the second of the second sec

Solder well single mating end 2nd contact grouping



## **Insert Material Specification:** Mil-p-19833, type gdi-30 military specification single material response single mating end **Unable To Decode:** Unable to decode and unable to decode **Included Contact Quantity:** 2 single mating end 1st contact grouping **Included Contact Type:** Round socket single mating end 2nd contact grouping **Special Features:** Coaxial contact terminals modified with a cap **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-p-19833 spec.