## NSN 5935-00-857-6692

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-857-6692 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 2.000 inches **Overall Height:** 0.840 inches **Overall Width:** 0.440 inches **Distance Between Mounting Facility Centers:** Between 1.683 inches and 1.693 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 16 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Polarization Method:** Guide pin/socket **Connector Locking Method:** Friction Thread Length: 0.156 inches Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end 2nd contact grouping **Contact Material:** Copper alloy single mating end 2nd contact grouping **Contact Surface Treatment:** Gold single mating end 2nd contact grouping **Insert Material:** Plastic diallyl phthalate glass filled single mating end

Terminal Type:

Solder well single mating end 2nd contact grouping

## NSN 5935-00-857-6692

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification
-------------------------------

Mil-p-19833, type gdi-30 military specification single material response single mating end

**Unable To Decode:** 

Unable to decode and unable to decode

**Included Contact Quantity:** 

2 single mating end 1st contact grouping

**Included Contact Type:** 

Round socket single mating end 2nd contact grouping

**Special Features:** 

Coaxial contact terminals modified with a cap

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.020 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

-

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.