

View Online at <https://aerobasegroup.com/nsn/5935-00-859-0449>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Electrical Insulation Feature:**

Insulated from panel

**Identification Code Color:**

Black

**Body Style:**

Threaded bushing mounted

**Overall Length:**

Between 0.915 inches and 0.925 inches

**Mounting Bushing Length:**

Between 0.370 inches and 0.380 inches

**Overall Diameter:**

Between 0.339 inches and 0.349 inches

**Bushing Accommodation Hole Shape:**

Round

**Maximum Voltage Rating In Volts:**

2000.0 ac

**Accommodated Finger Type:**

Test prod single finger

**Finger Accommodation Diameter:**

0.080 inches single finger

**Finger Accommodation Length:**

0.562 inches single finger

**Bushing Thru-hole Accommodation Diameter:**

Between 0.245 inches and 0.255 inches

**Current Rating In Amps:**

5.0

**Mounting Facility Type And Quantity:**

1 bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.250 inches

**Terminal Type:**

Turret

**Material:**

Plastic, polyamide insulator

**Material:**

Plastic polyamide insulator

Precious Material And Location:

Contact spring surface gold and contact spring surface silver

Precious Material:

Gold and silver

Surface Treatment:

Gold and silver spring

Surface Treatment:

Gold spring and silver spring

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03400