

View Online at <https://aerobasegroup.com/nsn/5935-00-865-0535>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.125 inches

**Overall Diameter:**

0.688 inches

**Distance From Mounting Shoulder To Front Face:**

0.688 inches

**Mounting Facility Thickness:**

0.062 inches

**Threaded Device Type:**

Coupling facility and mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Tnc single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Frequency Rating:**

10000.0 megahertz single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Connector Cable Strain Relief Method:**

Basket weave grip

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

28 and 28

**Thread Size:**

0.438 inches and 0.500 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Insert Material:**

Plastic tetrafluoroethylene single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Included Contact Quantity:**

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Shell surface silver

**Precious Material And Weight:**

0.100 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0