NSN 5935-00-865-3341



Electrical Receptacle Connector - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5935-00-865-3341	
Body Style:	
Straight shape, external coupling	
Overall Length:	
1.278 inches	
Overall Height:	
1.114 inches	
Overall Width:	
1.114 inches	
Environmental Protection:	
Corrosion resistant and vibration resistant and shock resistant and moisture resistant	
Unthreaded Mounting Hole Diameter:	
0.120 inches	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
0.812 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
0.812 inches	
Distance From Mounting Shoulder To Front Face:	
0.526 inches	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
12 single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
600.0 single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
310.0	
Shell Type:	
Solid	

Connector Locking Method:

Detent

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade a military specification single treatment response single mating end single contact grouping

NSN 5935-00-865-3341

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Chromate and cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Included Contact Quantity:
12 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.012 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-81703 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms3130 government standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No No
Fiig:
A039b0
Mil-std (military Standard):
Mil-q-45204 spec.