Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-865-7723

View Online at https://aerobasegroup.com/nsn/5935-00-865-7723
Thread Class:
2b
Thread Direction:
Right-hand
Overall Length:
1.469 inches
Overall Diameter:
1.250 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
16s-4 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
700.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1250.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
110.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Connector Cable Strain Relief Method:
Potting type
Thread Size:
1.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Solder well single mating and single contact grouping

Solder well single mating end single contact grouping

# NSN 5935-00-865-7723

Electrical Plug Connector - Page 2 of 2



#### **Shell Material:**

Aluminum alloy

# Shell Surface Treatment:

Cadmium

# Included Contact Quantity:

2 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

#### **Special Features:**

Grounding lug

#### **Precious Material And Location:**

Contact surface gold and contact surface silver

#### **Precious Material:**

Gold and silver

#### **Test Data Document:**

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Unef

# Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# Fiig:

A039b0