## NSN 5935-00-866-1573



Electrical Plug Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-866-1573 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling w/strain relief **Overall Length:** 1.781 inches Diameter: 1.343 inches **Overall Diameter:** 1.531 inches **Environmental Protection:** Corrosion resistant and moisture resistant and shock resistant and vibration resistant **Cable Entrance Diameter:** 0.640 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 21-30 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Cable clamp **Thread Size: 1.312** inches **Terminal Location:** 

Back single mating end single contact grouping

## **Contact Surface Treatment:**

Silver single mating end single contact grouping

## **Insert Material:**

Plastic single mating end

## **NSN 5935-00-866-1573**Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, class c federal specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Insert Material Specification:
Mil-p-17091 military specification single material response single mating end
Included Contact Quantity:
30 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.030 silver grains, troy
Precious Material:
Silver
Test Data Document:
81349-mil-c-25955 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Special acme
Specification Data:
96906-ms24235 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-p-17091 spec.