

View Online at <https://aerobasegroup.com/nsn/5935-00-866-2996>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

0.600 inches

Overall Height:

1.000 inches

Overall Width:

0.600 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end 1st contact grouping

Connector Locking Method:

Jackscrew

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Terminal Location:

Back single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold single mating end 1st contact grouping and silver single mating end 1st contact grouping

Insert Material:

Glass fiber single mating end and plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end 1st contact grouping and qq-s-365 federal specification 2nd treatment response single mating end 1st contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Solder well single mating end 1st contact grouping

Contact Material Specification:

Qq-b-626, comp 22 federal specification single material response single mating end 1st contact grouping

Shell Material:

Metal

Insert Material Specification:

Mil-p-19833, ty gdi-30 military specification all material responses single mating end

Included Contact Quantity:

30 single mating end 1st contact grouping

Special Features:

Polarizing pin located at contact positions j and g

Color:

Natural

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.030 gold grains, troy and 0.030 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.