NSN 5935-00-866-3008

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-866-3008

Body Style:

Straight edge type w/mounting flange

Overall Length:

4.279 inches

Overall Height:

0.660 inches

Overall Width:

0.343 inches

Environmental Protection:

Salt water resistant

Unthreaded Mounting Hole Diameter:

0.142 inches

Distance Between Mounting Facility Centers:

4.031 inches

Board Accommodated Length:

3.597 inches single board

Board Accommodated Width:

0.082 inches

Mating End Quantity:

Contact Position Arrangement Style:

Bridged contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type mdg military specification single material response single mating end

Included Contact Quantity:

22 single mating end single contact grouping

Included Contact Type:

Spring pincers single mating end single contact grouping

NSN 5935-00-866-3008

Electrical Receptacle Connector - Page 2 of 2



Precious	Material	And	Location:
----------	----------	-----	-----------

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.022 gold grains, troy and 0.022 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.