AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-866-6348

Thread C	lass:
2b	
Thread P	itch Diameters:
+1.801 to	1.812 inches
Thread D	irection:
Right-han	d
Body Sty	le:
Straight s	hape, internal coupling w/stra in relief
Body Ler	ngth:
Between	4.391 inches and 4.547 inches
Overall D	iameter:
Between	2.000 inches and 2.031 inches
Environn	nental Protection:
Humidity	resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant
Cable En	trance Diameter:
Between	1.172 inches and 1.203 inches
Threadec	I Device Type:
Coupling	facility
Mating E	nd Quantity:
1	
Contact I	Position Arrangement Style:
lc-v20 sin	gle mating end
Polarizat	ion Method:
Key, mul	tiple key groove
Insert Po	sition In Deg:
225.0	
Shell Typ	be:
Solid	
Connecto	or Locking Method:
Internally	threaded coupling ring
Connecto	or Cable Strain Relief Method:
Cable cla	mp
Thready	Qty Per Inch (tpi):
6	
Thread S	ize:
1.8125 ind	ches
Insert Ma	terial:
Plastic dia	allyl phthalate single mating end
Shell Mat	erial:
Aluminum	n alloy
Shell Sur	face Treatment:
Cadmium	



Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Insert Material Specification:

Mil-m-19833, ty gdi-30f military specification single material response single mating end

Thread Series Designator:

Special acme

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.