NSN 5935-00-868-6146

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-868-6146

Body Style:

Hood, top opening w/clamp

Overall Length:

Between 2.714 inches and 2.744 inches

Overall Height:

1.531 inches

Overall Width:

Between 0.479 inches and 0.509 inches

Environmental Protection:

Humidity resistant and moisture resistant and salt water resistant and vibration resistant

Cable Entrance Diameter:

1.375 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

"c, 27w2" single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

5.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end 2nd contact grouping

Contact Maximum Dc Voltage Rating In Volts:

3000.0 single mating end 1st contact grouping

Polarization Method:

Jackscrew

Shell Type:

Hood, top opening

Connector Locking Method:

Jackscrew

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and copper single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate single mating end

NSN 5935-00-868-6146Electrical Plug Connector - Page 2 of 2



Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-f-14072 military specification single treatment response
Insert Material Specification:
Mil-m-14, ty gdi-30f military specification single material response single mating end or mil-m-14, ty sdg-f military specification single material
response single mating end
Included Contact Quantity:
25 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.035 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.