Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-868-6248

view	Online at https://aerobasegroup.com/nsn/5935-00-868-6248
Threa	d Direction:
Left-ha	and
Overa	II Length:
1.578	inches
Overa	II Height:
1.750	inches
Overa	II Width:
1.750	inches
Enviro	onmental Protection:
Corros	sion resistant and explosion proof and shock resistant and vibration resistant
Cente	r To Center Distance Between Mounting Facilities Parallel To Height:
1.375	inches
Distar	nce Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.375	inches
Threa	ded Device Type:
Coupli	ing facility
Matin	g End Quantity:
1	
Conta	nct Maximum Current Rating In Amps:
46.0 s	ingle mating end single contact grouping
Conta	ct Maximum Ac Voltage Rating In Volts:
900.0	single mating end single contact grouping
Conta	ct Maximum Dc Voltage Rating In Volts:
1250.0	0 single mating end single contact grouping
Conne	ector Locking Method:
Extern	nally threaded shell
Threa	dy Qty Per Inch (tpi):
18	
Threa	d Size:
1.375	inches
Insert	Material:
Plastic	c single mating end
Shell	Material:
Alumir	num alloy
Includ	led Contact Quantity:
2 sing	le mating end single contact grouping
Incluc	led Contact Type:
Round	pin single mating end single contact grouping
Threa	d Series Designator:
Acme	
Shelf	Life:

N/a

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0