

View Online at <https://aerobasegroup.com/nsn/5935-00-868-8237>

**Body Style:**

Straight shape, external coupling w/backshell

**Overall Length:**

1.250 inches

**Overall Height:**

1.302 inches

**Overall Width:**

1.302 inches

**Environmental Protection:**

Corrosion resistant and vibration resistant and shock resistant and moisture resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.964 inches and 0.974 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.964 inches and 0.974 inches

**Distance From Mounting Shoulder To Front Face:**

0.542 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

27-3 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Detent

**Terminal Location:**

Back single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings and copper single mating end all contact groupings

**Terminal Type:**

Solder well single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Chromate and cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Included Contact Quantity:**

2 single mating end 1st contact grouping

**Included Contact Type:**

Round socket single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.016 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-milc26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-26482 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0