

View Online at <https://aerobasegroup.com/nsn/5935-00-869-2846>

Body Style:

Right angle type

Overall Length:

2.090 inches

Overall Height:

0.470 inches

Overall Width:

0.750 inches

Environmental Protection:

Thermal shock resistant and vibration resistant and shock resistant

Unthreaded Mounting Hole Diameter:

0.089 inches

Distance Between Mounting Facility Centers:

1.750 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

525.0 single mating end single contact grouping

Shell Type:

Solid

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tapered pin single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Insert Material Specification:

Mil-m-14f, ty mdg military specification single material response single mating end

Included Contact Quantity:

11 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.011 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14f spec.