NSN 5935-00-869-2846

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-869-2846 **Body Style:** Right angle type **Overall Length:** 2.090 inches **Overall Height:** 0.470 inches **Overall Width:** 0.750 inches **Environmental Protection:** Thermal shock resistant and vibration resistant and shock resistant **Unthreaded Mounting Hole Diameter:** 0.089 inches **Distance Between Mounting Facility Centers:** 1.750 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 525.0 single mating end single contact grouping Shell Type: Solid **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Tapered pin single mating end single contact grouping **Shell Material:** Aluminum **Shell Surface Treatment:** Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

NSN 5935-00-869-2846

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-14f, ty mdg military specification single material response single mating end

Included Contact Quantity:

11 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.011 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14f spec.