NSN 5935-00-869-3074

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-869-3074

Body Style:

Straight edge type w/mounting flange

Overall Length:

1.844 inches

Overall Height:

0.716 inches

Overall Width:

0.343 inches

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Mounting Facility Centers:

1.532 inches

Board Accommodated Length:

1.100 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping or beryllium single mating end single contact grouping and copper single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

Included Contact Quantity:

44 single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

NSN 5935-00-869-3074

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.044 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.