NSN 5935-00-869-4173

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-869-4173 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.125 inches **Overall Height:** Between 1.546 inches and 1.578 inches **Overall Width:** Between 1.546 inches and 1.578 inches **Environmental Protection:** Pressure proof **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** Between 0.600 inches and 0.675 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 22-55 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 30.0

Shell Type:

Solid

NSN 5935-00-869-4173

Electrical Receptacle Connector - Page 2 of 2



| Connector Locking Method: |
|---|
| Bayonet pin |
| Thread Size: |
| 1.312 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Insert Material: |
| Rubber synthetic single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Chromate |
| Included Contact Quantity: |
| 55 single mating end single contact grouping |
| Included Contact Type: |
| Hermaphrodite single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold and contact surfaces silver |
| Precious Material And Weight: |
| 0.055 gold grains, troy and 0.055 silver grains, troy |
| Precious Material: |
| Gold and silver |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |