NSN 5935-00-869-4548

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-869-4548 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.181 inches **Overall Height:** 1.782 inches **Overall Width:** 1.782 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.142 inches and 0.152 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.370 inches and 1.380 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.370 inches and 1.380 inches **Distance From Mounting Shoulder To Front Face:** 0.838 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 24-7 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 41.0 single mating end 1st contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end all contact groupings **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0

Shell Type:

Solid

NSN 5935-00-869-4548

Electrical Receptacle Connector - Page 2 of 2



| Connector Locking Method: |
|---|
| Externally threaded shell |
| Thread Length: |
| 0.625 inches |
| Thread Size: |
| 1.500 inches |
| Terminal Location: |
| Back single mating end all contact groupings |
| Contact Material: |
| Steel single mating end all contact groupings |
| Contact Surface Treatment: |
| Tin single mating end all contact groupings and cadmium single mating end all contact groupings |
| Terminal Type: |
| Solder stud single mating end all contact groupings |
| Shell Material: |
| Steel |
| Shell Surface Treatment: |
| Tin and cadmium |
| Included Contact Quantity: |
| 2 single mating end 1st contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Special Features: |
| Hermetically sealed |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |
| |