

View Online at <https://aerobasegroup.com/nsn/5935-00-869-4885>

Overall Length:

0.571 inches

Overall Height:

0.828 inches

Overall Width:

0.828 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.594 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.594 inches

Mating End Quantity:

1

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

End Application:

Armored vehicle launch bridge (m60a1 & m48a5); helicopter, search and rescue, hh-60h; helicopter, electronic countermeasures, eh-60a; helicopter, mh-53e; tank, combat, ft, 120mm gun (m1a1); helicopter, carrier based asw, sh-60f; chaparral/vulcan ads/ssamd; aircraft, (ac-130h, mc-130h, ec-130e, hc-1

Criticality Code Justification:

Feat

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Special Features:

Weapon system essential

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-26482 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.