

View Online at <https://aerobasegroup.com/nsn/5935-00-869-6613>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, flange mount, external coupling

Overall Height:

2.250 inches

Overall Width:

2.250 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.173 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.750 inches

Distance From Mounting Shoulder To Front Face:

0.875 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

32-7 single mating end

Contact Removability:

Nonremovable single mating end 3rd contact grouping

Contact Maximum Current Rating In Amps:

41.0 single mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end 3rd contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end 3rd contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

18 and 18

Thread Size:

1.750 inches and 2.000 inches

Terminal Location:

Back single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

7 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.063 gold grains, troy and 0.063 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Uns and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0