

View Online at <https://aerobasegroup.com/nsn/5935-00-869-6624>

**Body Style:**

Straight shape, pc type

**Overall Length:**

Between 4.345 inches and 4.375 inches

**Overall Height:**

Between 0.645 inches and 0.675 inches

**Overall Width:**

Between 0.345 inches and 0.355 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and shock resistant

**Distance Between Mounting Facility Centers:**

Between 4.050 inches and 4.060 inches

**Board Accommodated Length:**

3.591 inches single board and 3.601 inches single board

**Board Accommodated Width:**

Between 0.055 inches and 0.074 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Contact to contact polarizing keys

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, type sdg military specification single material response single mating end

**Included Contact Quantity:**

44 single mating end single contact grouping

**Included Contact Type:**

Leaf spring single mating end single contact grouping

**Special Features:**

Mtd by mtg provision no. 3; polarized at contact position 15

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.044 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.