

View Online at <https://aerobasegroup.com/nsn/5935-00-878-1502>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.280 inches

Overall Diameter:

0.797 inches

Cable Entrance Diameter:

0.219 inches

Distance From Mounting Shoulder To Front Face:

0.806 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

500.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

28

Thread Size:

0.500 inches

Terminal Location:

Back single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Terminal Type:

Crimp single mating end single contact grouping

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial socket single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0