NSN 5935-00-878-1705

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-878-1705 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Thru-hole mount **Overall Length:** 0.532 inches **Bushing Diameter:** 0.656 inches **Overall Diameter:** 0.719 inches **Environmental Protection:** Dustproof and moisture proof **Mounting Facility Thickness:** 0.125 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Mh-5 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Contact Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic melamine single mating end

Plastic melamine single mating **Terminal Type:**

Solder well single mating end single contact grouping

NSN 5935-00-878-1705

Electrical Receptacle Connector - Page 2 of 2



Contact Material Specification:

Qq-b-750, comp a, spring federal specification single material response single mating end single contact grouping

Included Contact Quantity:

5 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round keyed

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0