Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-878-2432

| aread Class: | |
|---|--------|
| | |
| read Direction: | |
| ght-hand | |
| ody Style: | |
| raight shape w/cable clamp | |
| verall Length: | |
| 312 inches | |
| ushing Diameter: | |
| 312 inches | |
| verall Height: | |
| 500 inches | |
| verall Width: | |
| 500 inches | |
| vironmental Protection: | |
| essure proof | |
| nthreaded Mounting Hole Diameter: | |
| 090 inches | |
| enter To Center Distance Between Mounting Facilities Parallel To He | ight: |
| 360 inches | |
| stance Between Centerlines Of Mounting Facilities Parallel To Body | Width: |
| 360 inches | |
| able Entrance Diameter: | |
| tween 0.216 inches and 0.222 inches | |
| stance From Mounting Shoulder To Front Face: | |
| 375 inches | |
| readed Device Type: | |
| pupling facility | |
| ating End Quantity: | |
| | |
| ontact Position Arrangement Style: | |
| onstd single mating end | |
| ontact Removability: | |
| premovable single mating end single contact grouping | |
| ontact Maximum Ac Voltage Rating In Volts: | |
| 0.0 single mating end single contact grouping | |
| nell Type: | |
| lid | |
| onnector Locking Method: | |
| ternally threaded shell | |
| onnector Cable Strain Relief Method: | |
| | |



Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

32

Thread Size:

0.312 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold and body surface silver

Precious Material And Weight:

 $0.005 \ \text{gold} \ \text{grains}, \ \text{troy} \ \text{and} \ 0.100 \ \text{silver} \ \text{grains}, \ \text{troy}$

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0