NSN 5935-00-878-4384

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-878-4384

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Hood, top opening w/clamp
Overall Length:
2.000 inches
Overall Height:
2.391 inches
Overall Width:
0.812 inches
Environmental Protection:
Corrosion resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
34 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Hood, top opening
Connector Locking Method:
Jackscrew-socket
Connector Cable Strain Relief Method:
Cable clamp
Cable Opening Length:
0.590 inches
Cable Opening Width:
0.440 inches
Thready Qty Per Inch (tpi):

NSN 5935-00-878-4384Electrical Plug Connector - Page 2 of 2



Thread Size:	
0.138 inches	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping and silver single mating end single contact grouping	
Insert Material:	
Plastic diallyl phthalate single mating end	
Terminal Type:	
Solder well single mating end single contact grouping	
Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Anodize	
Insert Material Specification:	
Mil-p-19833, ty gdi-30 military specification single material response single mating end	
Included Contact Quantity:	
34 single mating end single contact grouping	
Included Contact Type:	
Round socket single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold and contact surfaces silver	
Precious Material And Weight:	
0.034 gold grains, troy and 0.034 silver grains, troy	
Precious Material:	
Gold and silver	
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-p-19833 spec.	