## NSN 5935-00-878-7523

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-878-7523

Thread Class:	
2a and 2b and 2a	
Thread Direction:	
Right-hand and right-hand and right-hand	
Body Style:	
Straight shape	
Overall Length:	
1.250 inches	
Overall Height:	
0.530 inches	
Overall Width:	
0.270 inches	
Environmental Protection:	
Shock resistant and vibration resistant and corrosion resistant	
Distance Between Mounting Facility Centers:	
1.000 inches	
Threaded Device Type:	
Coupling facility and mounting stud	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
26 single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
3.0 single mating end single contact grouping	
Polarization Method:	
Jackscrew	
Connector Locking Method:	
Jackscrew-socket	
Thread Length:	
0.250 inches	
Thready Qty Per Inch (tpi):	

56 and 56 and 56

**Thread Size:** 

0.086 inches and 0.086 inches and 0.086 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

## NSN 5935-00-878-7523

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Insert Material Specification:
Mil-m-19833, ty gdi-30f military specification single material response single mating end
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
26 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Jackscrew type-female and location-right handandjackscrew type-male and location-left
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.026 gold grains, troy and 0.026 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unc and unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

hand