

View Online at <https://aerobasegroup.com/nsn/5935-00-878-7612>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Angle shape w/cable clamp

Overall Diameter:

1.969 inches

Body Angle In Deg:

90.0

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Cable Entrance Diameter:

0.922 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

28-9 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

41.0 single mating end 1st contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end all contact groupings

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Cable clamp

Distance From Centerline To Cable End:

2.188 inches

Thread Length:

0.594 inches

Thready Qty Per Inch (tpi):

18

Thread Size:

1.750 inches

Terminal Location:

Back single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

6 single mating end 1st contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.036 gold grains, troy and 0.036 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Specification Data:

81349-mil-c-5015 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0