

View Online at <https://aerobasegroup.com/nsn/5935-00-878-8628>

Body Style:

T-shape

Overall Length:

0.860 inches

Overall Height:

0.659 inches

Environmental Protection:

Shock proof and vibration proof and salt water resistant

Mating End Quantity:

3

Contact Position Arrangement Style:

Rf all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Current Rating In Amps:

1.5 all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Spring friction

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic all mating ends

Contact Surface Treatment Specification:

Mil-r-6855 military specification single treatment response all mating ends single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response all mating ends single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 2nd mating end single contact grouping

Included Contact Type:

Coaxial socket 1st mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.003 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-r-6855 spec.