

View Online at <https://aerobasegroup.com/nsn/5935-00-878-8628>

**Body Style:**

T-shape

**Overall Length:**

0.860 inches

**Overall Height:**

0.659 inches

**Environmental Protection:**

Shock proof and vibration proof and salt water resistant

**Mating End Quantity:**

3

**Contact Position Arrangement Style:**

Rf all mating ends

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Contact Maximum Current Rating In Amps:**

1.5 all mating ends single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Spring friction

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends single contact grouping

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping

**Insert Material:**

Plastic all mating ends

**Contact Surface Treatment Specification:**

Mil-r-6855 military specification single treatment response all mating ends single contact grouping

**Contact Material Specification:**

Qq-b-626 federal specification single material response all mating ends single contact grouping

**Shell Material:**

Copper alloy

**Included Contact Quantity:**

1 2nd mating end single contact grouping

**Included Contact Type:**

Coaxial socket 1st mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.003 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-r-6855 spec.