NSN 5935-00-879-1638

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-879-1638

Body Style:

Straight shape threaded

Overall Length:

0.719 inches

Overall Diameter:

Between 0.860 inches and 0.890 inches

Environmental Protection:

Heat resistant and sand resistant and vibration resistant

Distance From Mounting Shoulder To Front Face:

Between 0.438 inches and 0.468 inches

Mounting Facility Thickness:

0.063 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

12-p single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Spring friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Glass single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Shell Material:

Metal

Shell Surface Treatment:

Tin and cadmium

NSN 5935-00-879-1638

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 12 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.012 gold grains, troy **Precious Material:** Gold **Supplementary Features:** Mounting method - solder Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A039b0