

View Online at <https://aerobasegroup.com/nsn/5935-00-879-5373>

Body Style:

Straight shape, internal coupling

Overall Length:

0.938 inches

Overall Diameter:

0.375 inches

Environmental Protection:

Shock resistant and vibration resistant

Cable Entrance Diameter:

0.203 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Tps single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold and silver

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact and shell surfaces gold and contact and shell surfaces silver

Precious Material And Weight:

0.105 gold grains, troy and 0.105 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0