

View Online at <https://aerobasegroup.com/nsn/5935-00-879-7633>

Body Material:

Plastic and glass

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Top mount w/studs

Overall Length:

1.790 inches

Temperature Rating:

100.0 degrees celsius

Overall Height:

0.984 inches

Overall Width:

1.078 inches

Contact Maximum Current Rating In Amps:

1.0

Contact Material:

Phosphor bronze

Contact Surface Treatment:

Gold and silver

Accommodated Contact Quantity:

14

Missing Contact Designation:

6th contact position and 7th contact position and 8th contact position and 15th contact position and 16th contact position and 17th contact position

Polarization Type:

Off center hole

Saddle Material:

Steel

Saddle Surface Treatment:

Passivated

Projection Length Below Mounting Surface:

0.375 inches

Mounting Method:

Threaded stud

Mounting Type For Which Designed:

Chassis

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Contact Position Arrangement Style:

Concentric

Contact Maximum Voltage In Volts And Current Type:

500.0 ac

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.014 gold grains, troy and 0.014 silver grains, troy

Precious Material:

Gold and silver

Supplementary Features:

Item can be mounted above or below chassis

Thread Series Designator:

Unc

Terminal Type And Quantity:

14 solder well

Reference Number Differentiating Characteristics:

Fleet ballistic missile quality, as identified by quality control no. Poso 910900

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02300