

View Online at <https://aerobasegroup.com/nsn/5935-00-879-7633>

**Body Material:**

Plastic and glass

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Top mount w/studs

**Overall Length:**

1.790 inches

**Temperature Rating:**

100.0 degrees celsius

**Overall Height:**

0.984 inches

**Overall Width:**

1.078 inches

**Contact Maximum Current Rating In Amps:**

1.0

**Contact Material:**

Phosphor bronze

**Contact Surface Treatment:**

Gold and silver

**Accommodated Contact Quantity:**

14

**Missing Contact Designation:**

6th contact position and 7th contact position and 8th contact position and 15th contact position and 16th contact position and 17th contact position

**Polarization Type:**

Off center hole

**Saddle Material:**

Steel

**Saddle Surface Treatment:**

Passivated

**Projection Length Below Mounting Surface:**

0.375 inches

**Mounting Method:**

Threaded stud

**Mounting Type For Which Designed:**

Chassis

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Contact Position Arrangement Style:**

Concentric

**Contact Maximum Voltage In Volts And Current Type:**

500.0 ac

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.014 gold grains, troy and 0.014 silver grains, troy

**Precious Material:**

Gold and silver

**Supplementary Features:**

Item can be mounted above or below chassis

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

14 solder well

**Reference Number Differentiating Characteristics:**

Fleet ballistic missile quality, as identified by quality control no. Poso 910900

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02300